

# King Gage

## Single Tank Display System Prices and Options

**LevelPRO Tank Level Processor** Indicating tank level processor with 24Vdc power supply for sensor excitation. Use with typical two wire 4-20 mA DC sensor/transmitter. Requires nominal 100-240 Vac, 50/60 Hz. for operation. Enclosure for **wall mounting** intended to meet NEMA 4X.

Model Number	Description	Price
<b>4640-*</b>	Processor with Backlight LCD readout RS-485 communication, ASCII or ModBus protocol	\$1902.00
<b>4223</b>	Datapack iButton (application programming)	\$298.00

**\* Enclosure Selection Options**

- (2) NORYL plastic enclosure (standard)..... NC
- (3) 304 Stainless st enclosure option.....Add..... \$457.00

Indicating tank level processor with 24Vdc power supply for sensor excitation. Use with typical two wire 4-20 mA DC sensor/transmitter. Requires nominal 100-240 Vac, 50/60 Hz. for operation. Aluminum housing with flush Lexan front panel for **panel mounting**.

Model Number	Description	Price
<b>4640-1</b>	Processor with Backlight LCD readout RS-485 communication, ASCII or ModBus protocol	\$1654.00
<b>4223</b>	Datapack iButton (application programming)	\$298.00

Effective April 2004

1204 Main Street • Sebastian, Florida 32958  
Phone: 772-581-0477 • Fax: 772-581-0481

[www.wisnercontrols.com](http://www.wisnercontrols.com)

